



PRODUCT SPECIFICATIONS

Detail Photos

(on right from top to bottom)

Heavy-duty galvanized Az/El Mount

Fine azimuth and elevation adjustments

RF tested C-band Circular Polarized Feed assembly



2.4 m C-band Circular Polarized RxTx Class III Antenna System

TYPE 243

The Skyware Global Type 243 2.4 m Class III RxTx Antenna is a rugged commercial grade product suitable for the most demanding applications. The reflector is thermoset-molded for strength and surface accuracy. Molded into the rear of the reflector is a network of support ribs which not only strengthens the antenna, but also helps to sustain the critical parabolic shape necessary for transmit performance.

The Az/El mount is constructed from heavy-gauge steel to provide a rigid support to the reflector and feed support arm. Heavy-duty lockdown bolts secure the mount to any 168 mm (6.63") O.D. mast and prevent slippage in high winds.

Hot-dip galvanizing is standard on this model for maximum environmental protection.

- All materials comply with EU directive No. 2002/95/EC (RoHS).
- Two-piece precision offset thermoset-molded reflector.
- Heavy-duty galvanized Az/El mount.
- Fine Azimuth and elevation adjustments.
- Galvanized support arm and alignment struts.
- Factory pre-assembled mount.
- Plated hardware for maximum corrosion resistance.
- Includes C-band Circular Polarized RxTx Feed Assembly.
- Heavy-duty Class III mount for 11 kg (25 lb) RF electronics (LNB & BUC).

Type approved for use on Intelsat satellite system



BUY NOW

SPECIFICATIONS

Type 243 2.4 m C-band Circular Polarized RxTx Class III Antenna System

Type Approval Information

Antenna Model	62 - 2433411L Type N 62 - 2433911L (WR137)
Intelsat Standard	Standard G & H-2 (IESS 601)
Approval Code	IA051A00

(See Our Website for a Complete List of Type Approvals)

RF Performance

Effective Aperture	2.4 m (96 in)
Operating Frequency	Tx 5.850 - 6.425 GHz Rx 3.625 - 4.200 GHz
Polarization	Circular; Tx LH, Rx RH; or Tx RH, Rx LH
Gain (± 4 dBi)	Tx 42.2 dBi @ 6.1 GHz Rx 38.0 dBi @ 3.9 GHz
3 dB Beamwidth	Tx 1.3° @ 6.1 GHz Rx 2.1° @ 3.9 GHz
Sidelobe Envelope (Tx, Co-Pol dBi)	2° < θ < 48° 32 - 25 Log θ 48° < θ < 180° -10
Axial Ratio	Tx 1.3 VAR (2.3 dB) Rx 1.4 VAR (3.0 dB)
Antenna Noise Temperature	10° El 40° K 20° El 35° K 30° El 32° K
VSWR	Tx 1.3:1 Rx 1.5:1
Isolation (Port to Port)	Tx 80 dB Rx 70 dB
Feed Interface	Tx Type N or CPR-137 Rx CPR-229

(All specifications typical)

Mechanical Performance

Reflector Material	Glass Fiber Reinforced Polyester
Antenna Optics	Two-Piece Offset Feed Prime Focus
Mount Type	Elevation over Azimuth
Elevation Adjustment Range	10° - 90° Continuous Fine Adjustment
Azimuth Adjustment Range	360° Continuous $\pm 12'$ Fine Adjustment
Feed Support	Rectangular Section with Alignment Legs
Mast Pipe Interface	168 mm (6.63 in) Diameter
Wind Loading	Operational 80 km/h (50 mph) Survival 200 km/h (125 mph)
Temperature	-50°C to 80°C
Humidity	0 to 100% (Condensing)
Atmosphere	Standard Hardware Meets 500 Hour Salt Spray Test Requirements (ASTM B-117)
Solar Radiation	360 BTU/h/ft ²
Shock and Vibration	As Encountered During Shipping and Handling



Post Office Box 1639
101 Eagle Road - Building #7
Avon, Colorado, USA 81620
970 748-4250 - 866 SATCOM1
www.satcomresources.com



All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

VST-016.3

© 2012 Skyware Global